

Supplier	TOSHIBA
----------	---------

Appliance - Split type air conditioner

Outdoor unit	Single inverter	RAS-25S4AVPG-ND
Indoor unit	DAISEIKAI 10 R32	RAS-B25S4KVPG-ND

Function		Design load				Seasonal efficiency			
Cooling	Y	Cooling	Pdesignc	2.5	kW	Cooling	SEER	10.50	A+ ++
Heating - Average	Y	heating/Average	Pdesignh	3.0	kW	heating/Average	SCOP(A)	5.50	A+ ++
Heating - Warmer	N	heating/Colder	Pdesignh	4.5	kW				
Heating - Colder	Y					heating/Colder	SCOP(C)	4.60	A+ +
Capacity control	Variable								

Cooling

Capacity				Efficiency		
Declared capacity for cooling, at indoor temperature 27(19) °C and outdoor temperature Tj				Declared energy efficiency ratio, at indoor temperature 27(19) °C and outdoor temperature Tj		
Tj=35°C	Pdc	2.50	kW	Tj=35°C	EERd	5.90
Tj=30°C	Pdc	1.84	kW	Tj=30°C	EERd	8.90
Tj=25°C	Pdc	1.18	kW	Tj=25°C	EERd	14.60
Tj=20°C	Pdc	1.26	kW	Tj=20°C	EERd	16.83
				Degradation co-efficient cooling	Cdc	0,25

Heating (Average climate)

Capacity				Efficiency		
Declared capacity for heating/Average season, at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance/Average season, at indoor temperature 20 °C and outdoor temperature Tj		
Tj=-7°C	Pdh	2.65	kW	Tj=-7°C	COPd	3.65
Tj=2°C	Pdh	1.62	kW	Tj=2°C	COPd	5.67
Tj=7°C	Pdh	1.04	kW	Tj=7°C	COPd	6.90
Tj=12°C	Pdh	1.11	kW	Tj=12°C	COPd	7.25
Tj=bivalent temperature	Pdh	3.00	kW	Tj=bivalent temperature	COPd	3.00
Tj=operation limit	Pdh	2.40	kW	Tj=operation limit	COPd	2.10
Bivalent temperature		-10	°C			
Operation limit temperature		-30	°C	Degradation co-efficient heating	Cdh	0,25

Heating (Colder climate)

Capacity				Efficiency		
Declared capacity for heating/Colder season, at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance/Colder season, at indoor temperature 20 °C and outdoor temperature Tj		
Tj=-7°C	Pdh	2.72	kW	Tj=-7°C	COPd	3.65
Tj=2°C	Pdh	1.66	kW	Tj=2°C	COPd	5.67
Tj=7°C	Pdh	1.12	kW	Tj=7°C	COPd	6.90
Tj=12°C	Pdh	1.11	kW	Tj=12°C	COPd	7.25
Tj=bivalent temperature	Pdh	3.95	kW	Tj=bivalent temperature	COPd	3.10
Tj=operation limit	Pdh	2.40	kW	Tj=operation limit	COPd	2.10
Tj=-15°C	Pdh	3.95	kW	Tj=-15°C	COPd	3.10
Bivalent temperature		Tbiv	X	°C		
Operation limit temperature		Tol	X	°C		

Electricity

Electric power input in power modes other than active mode				Seasonal electricity consumption		
off mode	Poff	0.001	kW	Cooling	QCE	83 kWh/a
standby mode	Psb	0.001	kW	heating/Average	QHE/A	763 kWh/a
thermostat-off mode	Pto	0.028	kW	heating/Warmer	QHE/B	x kWh/a
Crankcase heater mode	Pck	0.000	kW	heating/Colder	QHE/C	2053 kWh/a

Refrigerant

Type	R32				
Weight				1.15	kg
Global Warming Potential	GWP			675	kgCO ₂ eq.

Sound power level - db(A)

Rated air flow - m³/h

	Cooling	Heating		Cooling	Heating
RAS-25S4AVPG-ND	59	60	RAS-25S4AVPG-ND	2220	2220
RAS-B25S4KVPg-ND	54	54	RAS-B25S4KVPg-ND	730	750

Dimensions

	Height	Width	Depth	Weight
RAS-25S4AVPG-ND	630 mm	800 mm	300 mm	43 kg
RAS-B25S4KVPG-ND	293 mm	930 mm	255 mm	14 kg

Harmonised standard	EN14511:2007 , EN12102
Calculation methods - Measurement standards	PrEN 14825: 2011 Chapter 8 and 9
Contact details for obtaining more information	Importer/Distributor in UK: Toshiba Carrier UK Ltd. Porsham Close, Belliver Industrial Estate, PLYMOUTH, Devon, PL6 7DB. United Kingdom

Carrier RLC Europe SAS
Authorised by Carrier Corporation as Toshiba HVAC products web site for Europe, Middle-East and Africa
A Carrier company
© 2025 Carrier. All rights reserved.



[Privacy notice](#) [Terms of use](#)